GEN. TOLERANCES	0.5 - 6	±0.1	6 - 30	±0.2	30 - 120	±0.3	120 - 315	±0.5	315 - 1000	±0.8	1000 - 2000	±1.2	2000 - 4000	±2	4000 - 8000	±3
GEN. MACHINING	√	0.4	√	1.6	√	3.2	√	6.3	√	12.6	√	25 ROUGH	√		√	



VIEW ON 'A' SHOWING DRILLING PATTERN AND OTHER DETAILS



GEAR DATA			
HARDENED GEAR			
NUMBER OF TEETH (z)		MODULE (m)	
PRESSURE ANGLE (∝)		DP	
ADDENDUM COEFFICIENT (x)			
PROFILE CORRECTION (xm)		CALCULATED GEAR STRENGTH	
TRUNCATION (km)		Fz (Normal)	KN
PITCH CIRCLE DIAMETER		Fz (Max)	KN
MEASUREMENT ON K TEETH		Pin Diameter	mm
RUNOUT NOT HARDENED/HARDENED			

Designed in accordance with designated QCB SLEWING RING STANDARDS
Non toleranced dimensions to ISO 2768-1 m
All burrs and sharp edges to be removed; Standard corner chamfer 1mm x 45°
Internal radial and axial clearance figures to QCB standard 2014 or revisions thereof
The HARDNESS GAP is to be indicated by stamped letter R or a PAINT mark on the exterior surface
The high point of gear eccentricity to be indicated by GREEN or BLUE paint on 3 teeth

BOLT DATA					
INNER	36 =	MOUNTING HOLES	Ø 14	AXIAL PLAY	0.10-0.22 mm
OUTER	36 =	MOUNTING HOLES	Ø 14	RADIAL PLAY	0.10-0.22 mm
GREASE HOLES	'G'		2 x 4 x M8	TURNING TORQUE	Nm
LOADING PLUG	'FS'	SOFT ZONE	'R'	MATERIAL	50Mn
		SEAL SIZE	TBA	WEIGHT	47 kg (est)
				DEPTH OF HARDENING (55-60HRc)	mm

© NBC GROUP LTD. NOT TO BE COPIED WITHOUT PERMISSION

REV	DATE	MODIFICATION	REVISED BY
1			

QCB Bearings
SLEWING RINGS & DRIVES
imported by NBC Group Ltd
Orleton Lane, Wellington, Telford, TF1 2BG, UK
P: 01952 222300 F: 01952 242938
www.nbcgroup.co.uk
QCB® is a registered trademark of NBC Group Ltd

QCB or NBC DRAWING NUMBER

SUN 716 X14 01 CC LM

QCB RS 11/2016

DRAWN:	LJM
DATE:	2/12/2015
CHECKED:	LJM